



















Selection Guide of Clamp Meters

AC Clamp Meters											
MODEL	2608A	2805	2006	2007A	2031	2017	2027	2040	2200	2002PA	2002R
Appearance											
Display	Analogue	Analogue	Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital
Sample rate	—	—	2 counts / sec	Approx. 2.5 counts / sec	2 counts / sec	Approx. 2.5 counts / sec	Approx. 2.5 counts / sec	3 counts / sec	2.5 counts / sec	Approx. 2.5 counts / sec	Approx. 2.5 counts / sec
Detection method	MEAN	MEAN	MEAN	MEAN	MEAN	MEAN	RMS	MEAN	MEAN	MEAN	RMS
Frequency response	50/60Hz	50/60Hz	40Hz~1kHz	40~400Hz	40Hz~1kHz	45Hz~1kHz	40Hz~1kHz	40~400Hz	45~65Hz(ACA) 45~600Hz(ACV)	40Hz~1kHz	40Hz~1kHz
Conductor size (MAX. mm)	φ 33mm	φ 35mm	φ 19mm	φ 33mm	φ 24mm	φ 33mm	φ 33mm	φ 33mm	φ 33mm	φ 55mm	φ 55mm
Measurement											
AC A Resolution	300A 0.2A	600A 0.2A	200A 0.001A	600A 0.1A	20A 0.01A	600A 0.1A	600A 0.1A	600A 0.1A	1000A 0.01A	2000A 0.1A	2000A 0.1A
DC A Resolution	—	—	—	—	—	—	—	—	—	—	—
ACV	600V	600V	500V	750V	—	600V	600V	600V	600V	750V	750V
DCV	60V	—	500V	—	—	—	—	600V	600V	1000V	1000V
Resistance	10kΩ	2kΩ	2kΩ	4000Ω	—	200Ω	200Ω	60MΩ	40MΩ	400kΩ	400kΩ
Continuity buzzer	—	—	○	○	—	○	○	○	○	○	○
Frequency	—	—	—	—	—	—	—	10kHz	—	—	—
DUTY	—	—	—	—	—	—	—	○	—	—	—
Diode test	—	—	—	—	—	—	—	○	—	—	—
Capacitance test	—	—	—	—	—	—	—	—	—	—	—
Temperature	-20~150°C	—	—	—	—	—	—	—	—	—	—
Function											
NCV	—	—	—	—	—	—	—	○	—	—	—
Back light	—	—	—	—	—	—	—	—	—	—	—
Data hold	○	○	○	○	○	○	○	○	○	○	○
Peak hold	—	—	—	—	—	—	—	—	—	○	○
MAX/MIN	—	—	—	—	—	—	—	○	—	—	—
REL	—	—	—	—	—	—	—	○	—	—	—
Output	—	—	—	—	—	—	—	—	—	DC400mV	DC400mV
Frequency filter	—	—	—	—	—	—	—	—	—	—	—
Water proof	—	—	—	—	—	—	—	—	—	—	—
Other											
Operating temperature	0~40°C	-10~50°C	0~50°C	0~40°C	0~40°C	-10~50°C	-10~50°C	0~40°C	0~40°C	0~40°C	0~40°C
Applicable standard	CAT. III 300V CAT. II 600V	—	—	CAT. III 300V CAT. II 600V	CAT. III 300V	CAT. III 600V	CAT. III 600V	CAT. IV 600V	CAT. III 600V (ACA) CAT. III 300V (AC/DCV) CAT. II 600V (AC/DCV)	CAT. III 600V CAT. II 1000V	CAT. III 600V CAT. II 1000V
Power source	R6P x 1	R6P x 1	R6P x 2	R03 x 2	LR-44 x 2	6F22 x 1	6F22 x 1	R03 x 2	R03 or LR03 x 2	R6P x 2	R6P x 2
Dimensions (L)x(W)x(D)mm	193 x 78 x 39	220 x 83 x 40	184 x 54 x 32	195 x 78 x 36	147 x 58.5 x 26	208 x 91 x 40	208 x 91 x 40	243 x 77 x 36	190 x 68 x 20	247 x 105 x 49	247 x 105 x 49
Weight (Approx.)	275g	390g	160g	260g	100g	400g	400g	300g	120g	470g	470g

Selection Guide of Clamp Meters

MODEL	AC/DC Clamp Meters								Fork Current Tester
	2010	2004	2033	2046R	2055	2056R	2003A	2009R	2300R
Appearance									
Display	Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital
Sample rate	Approx. 3 counts / sec	Approx. 3 counts / sec	Approx. 2.5 counts / sec	3 counts / sec	3 counts / sec	3 counts / sec	Approx. 2.5 counts / sec	Approx. 3 counts / sec	Approx. 2 counts / sec
Detection method	MEAN	MEAN	MEAN	RMS	MEAN	RMS	MEAN	RMS	RMS
Frequency response	DC, 40Hz~2kHz	DC, 40Hz~1kHz	DC, 20Hz~1kHz	DC, 40~400Hz	DC, 40~400Hz	DC, 40~400Hz	DC, 40Hz~1kHz	DC, 30Hz~1kHz	50/60Hz
Conductor size (MAX. mm)	φ 7.5mm	φ 19mm	φ 24mm	φ 33mm	φ 40mm	φ 40mm	φ 55mm	φ 55mm	φ 10mm
Measurement									
AC A Resolution	20A 0.1mA	200A 0.01A	300A 0.01A	600A 0.1A	1000A 0.1A	1000A 0.1A	2000A 0.1A	2000A 0.1A	100A 0.1A
DC A Resolution	20A 0.001A	200A 0.01A	300A 0.01A	600A 0.1A	1000A 0.1A	1000A 0.1A	2000A 0.1A	2000A 0.1A	100A 0.1A
ACV	—	500V	—	600V	600V	600V	750V	750V	—
DCV	—	200V	—	600V	600V	600V	1000V	1000V	—
Resistance	—	200Ω	—	60MΩ	60MΩ	60MΩ	4000Ω	4000Ω	—
Continuity buzzer	—	—	—	○	○	○	○	○	—
Frequency	—	—	—	10kHz	10kHz	10kHz	—	4000Hz	—
DUTY	—	—	—	○	○	○	—	—	—
Dioled test	—	—	—	○	○	○	—	—	—
Capacitance test	—	—	—	○	○	○	—	—	—
Temperature	—	—	—	○	—	○	—	—	—
Function									
NCV	—	—	—	○	○	○	—	—	○
Back light	—	—	—	○	○	○	—	—	—
Data hold	—	○	○	○	○	○	○	○	○
Peak hold	—	—	—	○	—	○	○	○	—
MAX/MIN	—	—	—	○	○	○	—	—	—
REL	—	—	—	○	○	○	—	—	—
Output	DC200mV	—	—	—	—	—	DC400mV	DC400mV	—
Frequency filter	—	—	—	—	—	—	—	—	—
Water proof	—	—	—	—	—	—	—	—	—
Other									
Operating temperature	0~50°C	-10~50°C	0~40°C	0~40°C	0~40°C	0~40°C	0~40°C	0~40°C	0~40°C
Applicable standard	—	—	CAT. III 300V	CAT. IV 600V	CAT. IV 600V	CAT. IV 600V	CAT. IV 600V	CAT. IV 600V CAT. III 1000V	CAT. III 300V
Power source	6LR61 x 1	R6P x 2	LR-44 x 2	R03 x 2	R03 x 2	R03 x 2	R6P x 2	R6 x 2	R03 x 2
Dimensions (L)x(W)x(D)mm	142 x 64 x 26(本体) 153 x 23 x 18(センサ)	180 x 54 x 32	147 x 59 x 25	243 x 77 x 36	254 x 82 x 36	254 x 82 x 36	250 x 105 x 49	250 x 105 x 49	161 x 40 x 30
Weight (Approx.)	220g	170g	100g	300g	310g	310g	530g	540g	110g

Selection Guide of Clamp Meters

Leakage Clamp Meters									
MODEL	2431	2432	2433	2433R	2412	2434	2417	2413F	2413R
Appearance									
Display	Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital
Sample rate	2 counts / sec	Approx. 2.5 counts / sec	Approx. 2.5 counts / sec	Approx. 2.5 counts / sec	Approx. 3 counts / sec	Approx. 2.5 counts / sec	Approx. 3 counts / sec	Approx. 3 counts / sec	Approx. 3 counts / sec
Detection method	MEAN	MEAN	MEAN	RMS	MEAN	MEAN	RMS	MEAN	RMS
Frequency response	40~400Hz	20Hz~1kHz	20Hz~1kHz	20Hz~1kHz	40~400Hz	40~400Hz	40Hz~1kHz	40Hz~1kHz	40Hz~1kHz
Conductor size (MAX. mm)	φ 24mm	φ 40mm	φ 40mm	φ 40mm	φ 40mm	φ 28mm	φ 40mm	φ 68mm	φ 68mm
Measurement									
AC A Resolution	200A 0.01mA	100A 0.001mA	400A 0.01mA	400A 0.01mA	500A 0.01mA	100A 0.1mA	500A 0.1mA	1000A 0.1mA	1000A 0.1mA
DC A Resolution	—	—	—	—	—	—	—	—	—
ACV	—	—	—	—	—	—	—	—	—
DCV	—	—	—	—	—	—	—	—	—
Resistance	—	—	—	—	—	—	—	—	—
Continuity buzzer	—	—	—	—	—	—	—	—	—
Frequency	—	—	—	—	—	—	—	—	—
DUTY	—	—	—	—	—	—	—	—	—
Diode test	—	—	—	—	—	—	—	—	—
Capacitance test	—	—	—	—	—	—	—	—	—
Temperature	—	—	—	—	—	—	—	—	—
Function									
NCV	—	—	—	—	—	—	—	—	—
Back light	—	—	—	—	—	—	—	—	○
Data hold	○	○	○	○	○	○	○	○	○
Peak hold	—	○	○	○	—	—	—	○	○
MAX/MIN	—	—	—	—	—	—	—	—	—
REL	—	—	—	—	—	—	—	—	—
Output	—	—	—	—	DC200mV	—	—	AC/DC200mV	AC/DC200mV
Frequency filter	○	○	○	○	○	○	○	○	○
Water proof	—	—	—	—	—	—	○	—	—
Other									
Operating temperature	0~40°C	0~40°C	0~40°C	0~40°C	0~40°C	0~40°C	0~40°C	0~40°C	0~40°C
Applicable standard	CAT. III 300V	CAT. III 300V	CAT. III 300V	CAT. III 300V	—	CAT. III 300V	CAT. III 300V	CAT. III 300V	CAT. III 300V
Power source	LR-44 x 2	R03 x 2	R03 x 2	R03 x 2	6F22 x 1	R03 x 2	6F22 x 1	6F22 x 1	6F22 x 1
Dimensions (L)x(W)x(D)mm	147 x 59 x 25	185 x 81 x 32	185 x 81 x 32	185 x 81 x 32	209 x 96 x 45	169 x 75 x 40	209 x 96 x 45	250 x 130 x 50	250 x 130 x 50
Weight (Approx.)	100g	290g	270g	270g	450g	220g	450g	570g	600g